# **TECHNICAL CHARACTERISTICS**


Gauge	200 mm
Ring diameter	127 mm
Number of spindles	30
Bobbin height	450 mm
Length Width Height	8400 mm 2500 mm 2500 mm
A different gauge a different ring diameter and a different number of spindles can be considered	

A different gauge, a different ring diameter and a different number of spindles can be considered. 3-draft machines (ST3) have gauge 300 mm only.

Gualchieri e Gualchieri reserve the right to modify the data in the tables without any notice in order to improve the machine performance.

# **TECHNICAL PERFORMANCES**

Max. draft (times)	999
Max. twists (tpm)	0-9999
Needle heads max. speed (rpm)	3500
Take-up ring spindles max. speed (rpm)	8800
Mechanical speed of core roller (m/min.)	185
Mechanical speed of feeding roller (m/min.)	185





SINCE 1973 MANY SOLUTIONS TO INCREASE YOUR BUSINESS EFFICIENCY

Fanta ROC-FIL

Fanta EXTRA

Fanta ROC

Fanta SPIN

Fanta ROC-FT2

EPT CHENILLE

Fanta BFL

Spike FILO-AIR

Fanta FILO

Spike FILO-IB




Spike EXTRA-FT

#### **GUALCHIERI e GUALCHIERI**

Via delle Fonti, 393/U - 59100 PRATO - ITALY Phone +39 0574 590587 - Fax +39 0574 577759 info@gualchieriegualchieri.it







MADE IN ITALY WITH PASSION SINCE 1973



# Spike FILO-AIR

### THE LIGHTNESS OF SOFTKNIT YARN

Machine for the production of soft knitted fancy yarns by means of needle heads with air jet. The yarn is taken-up on bobbin. Optimized mechanical ratios to guarantee high feeding speeds.

## **WORKING MODALITIES**


# spike FILO

- Needle head
- Take-up on bobbin



## MAIN MACHINE SPECIFICATIONS

- PLC to control the machine
- Control panel on board the machine
- Efficient control software
- Simple and intuitive graphical interphace
- Working modality selectable from the software
- Storage of the working programmes
- Diagnostics for the machine status
- Remote assistance



# **OPTIONAL ACCESSORIES**

- Hollow spindles
- Insertion bars for heads with 1 working position
- Final yarn detectors
- Stop-motions for core yarns



## **FEEDING**

**ST:** from roving or sliver

- ST1 (1 draft)
- ST2 (2 drafts). Patented. Suitable also for short fibres (cotton type)
- ST3 (3 drafts)



## NEEDLE HEAD

- 1 working position
- 2 working positions



# RING SPINDLE

Take-up bobbin

