



HIGH TEMPERATURE STEAMING EQUIPMENT 高温蒸化锅



整机外观图
The appearance of machine

产品用途：

国内专业设计、制造·全自动高温高压蒸化锅，适用于：化纤、真丝、棉纱、缝纫线、羊绒、窗帘折皱、起皱布、印花布、花边、商标、毛巾等高温高压固色、定型。特别是涤纶超纤维替代腈纶材料的毛毯、地毯的固色定型效果更佳。

产品特性：

- ◇ 自动化程度高，操作控制简便
- ◇ 温度均匀、保温性好、升温快
- ◇ 蒸化质量稳定、效果好
- ◇ 容量大、安全、可靠、节能
- ◇ 轨道式进出织物、劳动强度低

技术特性：

- ◇ 卧式圆筒型：直径Φ2600mm Φ2900mm
 - ◇ 密封形式：气封（压缩空气）
 - ◇ 加热方式：蒸汽直接加热（可增加间接加热）
 - ◇ 国内最高工作压力：0.30MPa
 - ◇ 工作温度：135℃
 - ◇ 主要受压材料：Q235B
 - ◇ 上顶设有不锈钢挡水板
- 注：可根据客户要求订制各规格

rapid temperature rises:

Professional design and manufacture in China. The high temperature and high pressure steaming equipment suitable for dye fixation and setting of chemical fiber, silk, cotton yarn, sewing thread, cashmere, curtain crease, cockled cloth, printed cloth, lace, trademark, towels. Especially it provide better fixation and setting effect of blanket and carpet which is made of polyester microfiber instead of acrylic fiber.

Product features:

- ◇ High automation, simple operation and control
- ◇ Temperature uniformity, good heat preservation, heating fast
- ◇ Stable steaming quality and good efficiency
- ◇ Large capacity, safe, reliable, energy saving
- ◇ Fabric input and output in track type, low labor intensity



Technical characteristics:

- ◇ Horizontal cylinder: Φ2600mm Φ2900mm
 - ◇ Seal type: air seal (compressed air)
 - ◇ Heating type: direct steam heating (could increase the indirect heating)
 - ◇ Maximum working pressure: 0.30Mpa
 - ◇ Working temperature: 135℃
 - ◇ Main pressure material: Q235B
 - ◇ The top is provided with a stainless steel water retaining plate
- Note: could be customized according to customer requirements of various specifications