

NEW

Batching unit

GROB
passion in winding

▶REVO◀

LOW ENERGY



High Capacity winder

Diameter: **1'500** mm

Weight: **2'000** kg

The Willy Grob batching unit type **▶REVO◀** is specially designed for applications in the field of mass production of standard fabrics such as Denim, apparel fabrics, general cotton or terry towel textiles etc.

The **▶REVO◀** convinces due to its **extraordinary price/performance ratio** without compromising in terms of machine and winding quality. Equipped with the latest drive technology as well as a convenient and easy operation system, this new compact batching unit allows the production of first class cloth rolls at **lowest power consumption**.









Composed as a universal device, the **▶REVO◀** can be installed behind all established weaving machine makes and permits the choice of different additional options thanks to the modular architecture.

Innovation
Switzerland

Willy Grob Ltd.
alte Schmerikonerstrasse 3
8733 Eschenbach (SG)
Switzerland

Tel: ++41 55 286 13 40
Fax: ++41 55 286 13 50
info@willy-grob.ch
www.willy-grob.ch

Technical sheet, options:

| | Description | REVO |
|---|---|-------------|
| ∅ | Max. batch diameter [mm] | 1'500 |
| ←→ | Nominal weaving machine width [cm] | 190 ... 230 |
| ▶ | Velocity [m/min.] | up to 2.0 |
| P | Input rating [kW] | 0.18 |
|  | Connection to weaving machine | ✓ |
|  | Selectable cloth tension 100 N to 800 N | ✓ |
| AS | Anti-slip-function during winding | ✓ |
| AT | Anti-traction during weaving machine stop | ✓ |
|  | Emergency button | ✓ |
| Options | | |
|  | Ejecting device – manual electric | ○ |
|  | Inspection table (straight, inclined, with or without illumination) | ○ |
|  | 'Touch-Screen' operating panel | ○ |
|  | Digital speed limiter 'AS' ['TS' required] | ○ |
|  | Meter counter ['TS' required] | ○ |
| | Fabric spreading system | ○ |
| | Cloth beam (aluminum – synthetic) | ○ |

✓ standard
○ option

Factsheet:

- cloth tension freely adjustable ▶ at any time
- absolute constant tension ▶ uniform cloth tension from empty to full batch!
- winding speed up to 2.0 m/min
- installation independent from weaving machine make
- maintenance-free
- compact and clearly arranged construction
- convenient operating system
- latest frequency-converter technology

handed over by: